



US010267312B2

(12) **United States Patent**
Pohler

(10) **Patent No.:** **US 10,267,312 B2**
(45) **Date of Patent:** ***Apr. 23, 2019**

(54) **LIQUID PUMP**

(71) Applicant: **Liberty Pumps, Inc.**, Bergen, NY (US)

(72) Inventor: **Donald M. Pohler**, North Chili, NY (US)

(73) Assignee: **Liberty Pumps, Inc.**, Bergen, NY (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 9 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/661,472**

(22) Filed: **Jul. 27, 2017**

(65) **Prior Publication Data**

US 2017/0321701 A1 Nov. 9, 2017

Related U.S. Application Data

(63) Continuation of application No. 13/739,041, filed on Jan. 11, 2013, now Pat. No. 9,719,515.

(51) **Int. Cl.**

F04D 1/00 (2006.01)

F04D 29/62 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **F04D 1/00** (2013.01); **F04D 7/045** (2013.01); **F04D 29/167** (2013.01); **F04D 29/426** (2013.01); **F04D 29/628** (2013.01)

(58) **Field of Classification Search**

CPC F04D 1/00; F04D 7/045; F04D 29/167; F04D 29/426; F04D 29/628; F04D 29/2288; B02C 18/0092

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,928,795 A 10/1933 Reid
3,154,019 A * 10/1964 Hoyt F04D 13/10
415/112

(Continued)

FOREIGN PATENT DOCUMENTS

CN 201982345 U 9/2011

OTHER PUBLICATIONS

Pentair Myers Model MRG20 Grinder Pump Installation and Service Manual, product document dated Nov. 8, 2012. EFS file name 201708xx_15-661472_IDS_NPL_Cite1.pdf.

(Continued)

Primary Examiner — Carlos A Rivera


Assistant Examiner — Eric J Zamora Alvarez

(74) *Attorney, Agent, or Firm* — John M. Hammond; Patent Innovations LLC

(57) **ABSTRACT**

A pump for pumping liquids containing entrained solids. The pump is comprised of a volute surrounding an impeller comprising vanes that are self-cleaning. The outer surfaces of the vanes are coplanar and define a first plane and have a leading edge. The volute is comprised of a planar mating surface defining a second plane parallel to the first plane of the rotary impeller. The planar mating surface is proximate to the outer surfaces of the vanes and is comprised of a plurality of channels extending radially from the inner perimeter to the outer perimeter thereof. Each channel includes a forward edge in the direction of impeller rotation. The channels are oriented such that when the impeller is rotated within the volute, for any vane, the leading edge of the vane traverses each channel progressively from the inner end of the channel to the outer end of the channel.

5 Claims, 11 Drawing Sheets



- (51) **Int. Cl.**
F04D 7/04 (2006.01)
F04D 29/16 (2006.01)
F04D 29/42 (2006.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,155,046 A 11/1964 Vaughan
3,526,465 A * 9/1970 Compton F04D 9/002
415/121.2
3,650,481 A * 3/1972 Conery B02C 18/0092
241/257.1
4,454,993 A * 6/1984 Shibata F04D 7/045
241/46.017
4,778,336 A * 10/1988 Husain F04D 7/045
241/46.06
5,044,566 A * 9/1991 Mitsch F04D 7/045
241/259.3
5,122,032 A 6/1992 Shields et al.
5,156,522 A * 10/1992 Tessier F04D 29/167
415/170.1
5,256,032 A * 10/1993 Dorsch F04D 7/045
415/121.1
5,460,482 A 10/1995 Dorsch
5,478,222 A 12/1995 Heidelberg
5,713,719 A 2/1998 Fiore
6,190,121 B1 * 2/2001 Hayward F04D 7/045
415/121.1
7,118,327 B2 * 10/2006 Doering F04D 7/045
415/121.1
7,125,221 B2 * 10/2006 Dorsch F04D 7/045
415/121.1

7,159,806 B1 * 1/2007 Ritsema B02C 18/0092
241/258
7,237,736 B1 * 7/2007 Martin F04D 7/045
241/185.6
7,537,439 B2 5/2009 Pohler
7,841,826 B1 * 11/2010 Phillips E21B 43/128
415/121.1
8,109,714 B2 * 2/2012 Keener F04D 29/2288
241/46.06
8,109,730 B2 * 2/2012 Andersson F04D 29/2288
415/121.1
8,267,643 B2 * 9/2012 Wagner F04D 7/045
415/121.1
2004/0136826 A1 7/2004 Britt
2012/0207590 A1 8/2012 Pohler
2013/0121811 A1 * 5/2013 Cuppetelli F04D 29/2288
415/121.1
2013/0243634 A1 * 9/2013 Ciro F04D 7/04
418/1
2014/0199165 A1 * 7/2014 Pohler F04D 7/045
415/204

OTHER PUBLICATIONS

ABS "S" Series 2—4hp Piranha Grinder Pump product literature, product document pdf Created: Jul. 13, 2000. EFS file name 201708xx_15-661472_IDS_NPL_Cite2.pdf.
Jung Pumpen G2DT/G2D-Series product literature, product document pdf Created: Dec. 7, 2010. EFS file name 201708xx_15-661472_IDS_NPL_Cite3.pdf.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6





FIG. 7






FIG. 9A

PRIOR ART




FIG. 9B




FIG. 9C






FIG. 9D






FIG. 10C




FIG. 10D




FIG. 10E

1

LIQUID PUMP

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS

This application is a continuation of copending U.S. patent application Ser. No. 13/739,041, filed on Jan. 11, 2013, the disclosure of which is incorporated herein by reference.

BACKGROUND

Technical Field

Pumps for the transfer of liquids; more particularly, centrifugal pumps, and centrifugal grinding pumps.

Description of Related Art

A pump is a device used to transport liquid from a lower to a higher elevation, or from a vessel of lower pressure to a vessel of higher pressure, or to a state of low velocity to a state of high velocity. Generally, in transporting a liquid, a pump adds energy to the liquid. Typically, an electric motor or other suitable motor is used to spin an impeller or other liquid driver inside a volute casing, transferring energy to the liquid. In many instances, a pump is submerged in a pool and its discharge is connected to a pipe that is used to convey the liquid to a higher elevation. Although pumps have been known for millennia, and advances in the design and manufacturing of pumps have continued right up to the present, there remain opportunities for improvement in many aspects of pump design, such as efficiency, reliability, and manufacturing cost.

This applies to centrifugal pumps, and to grinder pumps. A grinder pump is a pump that reduces the size of solid objects suspended in the liquid. In a typical grinder pump, a cutting or grinding device is incorporated into the suction opening of the pump, which chops or reduces the size of solid objects as the pump moves the liquid. The design of the cutting/grinding device varies by manufacturer, but in essentially all centrifugal grinder pumps, the slurry from the cutting/grinding device is drawn from the cutting apparatus to the eye of an impeller. Under normal operation, the slurry passes through the impeller vanes and volute casing without problems; however problems often do occur.

Solid debris from the slurry often accumulates between the vanes of the impeller and the stationary volute casing, causing undesired friction and load on the pump motor, which reduces the efficiency of the pump. In the worst cases, the debris may block an entire vane passageway or jam the impeller. In one attempt to address this problem, long "record" (spiral) grooves are formed in the volute base surface that is proximate to the impeller vanes in an attempt to cause accumulated material to be shed from the impeller, or prevent accumulation of material on the impeller. These record grooves are of limited effectiveness, particularly with certain types of solid materials in the slurry. What is needed to address this problem is a more reliable and effective means of shedding accumulated solid material from a pump impeller and/or preventing solid material from accumulating on the impeller, which would increase the reliability and efficiency of a grinder pump.

A critical component in any liquid pump is the seal that prevents liquid from leaking from the volute along the rotating shaft into the housing that contains the pump motor. Typically a mechanical face seal is used that is comprised of

2

two ground surfaces riding on each other with a very thin layer of liquid between them as a lubricant. Foreign material suspended in the liquid or long fibrous strands can either wrap around the seal, thereby forcing it open or eroding one or both of the ground surfaces. In either case, the seal is damaged. This is particularly the case in a grinder pump application, where the seal is exposed to a liquid slurry containing suspended solids. There remains a need for extending the life of a seal in a grinder pump, which would increase the reliability and reduce the maintenance cost of the pump while avoiding the additional cost of downtime of the pumping process.

In a related aspect, a pump may be damaged if it is run dry, even if for only a short period of time. In particular, the seal may be damaged by running the pump without having adequate liquid in the volute to maintain the seal in a wet condition. There remains a need for a pump that can be run in a dry state for a more prolonged period of time, thereby extending seal life.

The cost of energy is becoming an increasingly important consideration when selecting a pump for a given application. There remains a need for improving the efficiency of pumps, including grinder pumps, so that a given pumping output may be attained with less energy consumption by the pump.

Manufacturing cost and manufacturing precision are also important considerations in pump selection. Greater manufacturing precision results in greater pump reliability, and lower manufacturing cost results in lower purchase cost for the end user. The basic structure of a centrifugal grinder pump has remained quite complex, in that the pump includes a pump motor housing, a multi-piece pump volute, and a grinding device, which are expensive to manufacture individually, and to assemble in a reliable manner. Hence there remains a need for a pump having fewer components that are lower in cost to manufacture and assemble, and which can be assembled with greater precision, thereby resulting in greater pump reliability.

SUMMARY

In accordance with the present disclosure, in a pump, the problem of shedding accumulated solid material from a pump impeller and/or preventing solid material from accumulating on the impeller is solved by a pump that comprises a rotary impeller and a volute having particular features. The impeller is comprised of a flange surrounding a central hub. The flange includes a plurality of vanes, each vane extending radially from the hub and having an inner vane end, an outer vane end, and an outer surface. The outer surfaces of the vanes are coplanar and define a first plane and have a leading edge. The volute surrounds the impeller and is comprised of a planar mating surface defining a second plane parallel to the first plane of the rotary impeller. The planar mating surface is proximate to the outer surfaces of the vanes and has an inner perimeter forming an inlet opening of the volute and an outer perimeter. The planar mating surface is further comprised of a plurality of channels extending radially from an inner channel end at the inner perimeter to an outer channel end at the outer perimeter. Each of the channels includes a forward edge in the direction of impeller rotation. The channels are oriented such that when the impeller is rotated within the volute, for any vane, the leading edge of the vane traverses each channel progressively from the inner end of the channel to the outer end of the channel.

In certain embodiments, the vanes and the channels may be arcuate in shape with the leading edges of the vanes being convex edges, and the forward edges of the channels also

being convex edges. In such a configuration, the angle of intersection of any vane with any channel decreases during progression of the intersection from the inner channel end to the outer channel end. During rotation of the impeller, the angle of intersection of any vane with any channel may transition from an obtuse angle to an acute angle.

In certain embodiments, the inner vane ends may be contiguous with the central hub. The outer vane ends may be contiguous with the outer perimeter of the flange. The outer ends of the vanes may extend radially beyond the outer perimeter of the planar mating surface of the volute. The number of vanes may vary between 1 and 11, and the number of channels may vary between 1 and 9. The number of vanes may be at least equal to the number of channels.

In certain embodiments, the distance between the outer surfaces of the impeller vanes and the planar mating surface of the volute may be between 0.005 inches and 0.06 inches. Having a minimal vane-to-mating surface is advantageous with respect to pump efficiency, and in some embodiments, the clearance may be lesser. In some embodiments, the width of the outer surfaces of the vanes may be between 0.125 inches and 0.5 inches, and the width of the channels may be between 0.08 and 0.12 inches.

In certain embodiments, the planar mating surface may be further comprised of a plurality of stub channels, each of the stub channels extending from the inner perimeter of the planar mating surface to between one quarter and one half of the distance to the outer perimeter of the planar mating surface.

In another aspect of the Applicants' liquid pump, the problem of reducing pump manufacturing and assembly cost while enabling greater precision of pump assembly is solved by providing a unitary pump volute formed as a single piece and comprising certain features. The volute of the pump is comprised of a volute chamber comprised of an upper wall, a side wall and a lower wall. A first annular structure extends upwardly from the upper wall of the volute chamber and is comprised of a cylindrical cavity having a first annular side wall and a bottom wall. A cylindrical passageway extends from the bottom wall of the cylindrical cavity to the volute chamber. The cylindrical passageway may be partially bounded by a second annular side wall which terminates at a planar bottom surface. A second annular structure surrounds the first annular structure, and extends upwardly from the upper wall of the volute chamber. The second annular structure may be comprised of an outer cylindrical wall. A planar flange also surrounds the first annular structure. The inner perimeter of the planar flange may be contiguous with the outer cylindrical wall of the second annular structure. A through opening is provided in the lower wall of the volute chamber to enable the installation of an impeller on a pump motor shaft, and to enable access to the impeller if maintenance of the pump is needed.

The pump is further comprised of a motor housing joined to the pump volute. The motor housing is comprised a lower planar surface contiguous with the planar flange of the pump volute. With regard to the pump volute, the first annular side wall, the cylindrical passageway, and the outer cylindrical wall have collinear central axes defining a common central axis. The bottom wall of the cylindrical cavity, the planar bottom surface, and the planar flange define planes parallel to each other and perpendicular to the central axes. These features enable reducing the pump manufacturing and assembly cost while enabling greater precision of assembly of the pump and greater pump reliability as will be explained subsequently in this disclosure.

In another aspect of the Applicants' liquid pump, the problem of extending the life of a seal in the pump is solved by providing a pump volute, a rotary shaft, and a rotary impeller including certain features. The volute is comprised of a volute chamber having an upper wall including an annular recess surrounding a downward annular structure, and a passageway extending through the downward annular structure. The rotary shaft extends through the passageway into the volute chamber. The rotary impeller is joined to the rotary shaft and is comprised of a flange including an upward annular structure extending into the annular recess of the upper wall of the volute chamber.

The seal is fitted to a lower edge of the downward annular structure and prevents the leakage of fluid from the volute into the motor and/or a housing containing the motor. The location of the seal on the lower edge of the downward annular structure positions it such that it is disposed within the passageway and surrounds a portion of the rotary shaft. The lower portion of the seal extends into an annular cavity that is formed between the rotary shaft and the upward annular structure of the impeller. In that manner, if the pump temporarily runs dry or takes in some air, the seal remains wetted, lubricated, and cooled by at least some liquid, thereby preventing damage to the seal and extending its life. Additionally, the downward annular structure and the annular recess coact to prevent solids in a liquid slurry in the volute from reaching the seal while maintaining the seal in a wet condition. This also prevents damage to the seal and extends its life.

In another of the Applicants' liquid pump configured as a grinder pump, the problem of increasing pump efficiency by reducing energy consumption is solved by a solids cutting assembly that has reduced operating friction and reduced drag in the liquid to be pumped. Thus the pump requires less energy to accomplish the same amount of solids grinding and liquid pumping. The cutting assembly is comprised of a rotatable drive shaft and a rotary cutter joined to the drive shaft and comprised of a frustoconical hub having a circular planar hub base, and a first cutting blade and a second cutting blade.

Each of the cutting blades is comprised of a planar blade base defining a cutting plane and terminating at a cutting edge extending tangentially outwardly from the circular planar hub base. At any radial distance along each cutting blade, the ratio of the width of the cutting blade to the thickness of the cutting blade at that radial distance is at least is at least about two, and preferably at least about three. Additionally, at any radial distance along each cutting blade, the maximum thickness of the cutting blade is located at least 70 percent of the distance across the cutting blade in the direction opposite the direction of rotation.

The pump is further comprised of a cutter plate comprising an outer planar cutter surface parallel to and proximate to the cutting plane of the cutting blades. Rotary motion of the rotary cutter creates a shearing region between the cutting edges of the cutter and the cutter surface.

The first and second cutting blades may be further comprised of a first angled outer surface terminating at the cutting edge. In such a configuration, the first angled outer surface is on the leading side of the blade with respect to the direction of cutter rotation and may form an acute angle with the blade base of less than 45 degrees. The first and second cutting blades may be further comprised of a second angled outer surface terminating at the blade base. In such a configuration, the second angled outer surface is on the trailing side of the blade with respect to the direction of

cutter rotation and may form an approximately perpendicular or obtuse angle with the blade base.

BRIEF DESCRIPTION OF THE DRAWINGS

The present disclosure will be provided with reference to the following drawings, in which like numerals refer to like elements, and in which:

FIG. 1 is a side elevation view of one embodiment of the Applicants' pumps provided as a grinder pump;

FIG. 2 is a lower perspective view of the pump of FIG. 1, depicting the lower portion of the pump volute, grinder cutter plate, and cutter;

FIG. 3 is a side cross-sectional view of the pump of FIG. 1;

FIG. 4 is a detailed cross-sectional view of the volute, impeller, and cutter of the pump of FIG. 1;

FIG. 5 is a lower perspective view of a pump impeller;

FIG. 6 is an upper perspective view of a plate that forms the lower portion of the volute of the pump;

FIG. 7 is a cross sectional view of the pump volute, impeller, and lower volute plate of the pump of FIG. 1, taken along the line 7-7 of FIG. 1;

FIG. 8 is an exploded perspective view of a pump volute, impeller, and lower volute plate of certain embodiments of the Applicants' pumps;

FIGS. 9A-9D are views of a cutter and cutter plate of a prior art grinder pump presented for comparison to embodiments of the Applicants' grinder pump;

FIG. 10A is a lower perspective view of a cutter and cutter plate of the Applicants' grinder pump;

FIG. 10B is a bottom view of the cutter and cutter plate of the pump of FIG. 10A, taken along the line 10B-10B of FIG. 10A;

FIG. 10C is a cross-sectional view of a blade of the cutter of the pump of FIG. 10A, taken along the line 10C-10C of FIG. 10B;

FIG. 10D is a side elevation view of the cutter of the pump of FIG. 10A, taken along the line 10D-10D of FIG. 10B; and

FIG. 10E is a perspective view of the underside of the cutter of the pump of FIG. 10A.

The present invention will be described in connection with certain preferred embodiments. However, it is to be understood that there is no intent to limit the invention to the embodiments described. On the contrary, the intent is to cover all alternatives, modifications, and equivalents as may be included within the spirit and scope of the invention as defined by the appended claims.

DETAILED DESCRIPTION

For a general understanding of the present invention, reference is made to the drawings. In the drawings, like reference numerals have been used throughout to designate identical elements. In the following disclosure, certain components of the invention may be identified with adjectives such as "top," "upper," "bottom," "lower," "left," "right," etc. These adjectives are provided in the context of use of the Applicants' pumps in a position in which the axis of pump impeller rotation is vertical, and/or in the context of the orientation of the drawings, which is arbitrary. The description is not to be construed as limiting the Applicants' pumps to use in a particular spatial orientation. The instant pumps may be used in orientations other than those shown and described herein.

Additionally, certain embodiments of the Applicants pumps are described with the drawings showing a "grinder

pump," i.e., a pump that is used to macerate solids entrained in the liquid to be pumped. It is to be understood that these embodiments are not limited to being only applicable to grinder pumps, but instead are applicable to any pumps comprised of a rotary impeller surrounded by a volute.

Referring first to FIGS. 3-8, in one aspect of the Applicants' pump, the problem of shedding accumulated solid material from a pump impeller and/or preventing solid material from accumulating on the impeller is solved by a pump 10 that comprises a rotary impeller 100 and a volute 200 having particular features. The impeller is comprised of a flange 110 surrounding a central hub 120. The flange 110 may include a plurality of vanes 130. Each vane 130 extends radially from the hub 120 and has a proximal end 132, a distal end 134, and an outer surface 136. The outer surfaces 136 of the vanes 130 are coplanar and define a first plane. Each of the vanes 130 has a leading edge 138, which bounds the vane outer surface 136 in the direction of impeller rotation indicated by arrows 139.

The volute 200 surrounds the impeller 100 and is comprised of a planar mating surface 252 defining a second plane that is parallel to the first plane of the rotary impeller 100. In certain embodiments, the planar mating surface 252 is provided on the inner side 251 of a removable volute bottom cover 250, which is fitted to a circular or cylindrical cover opening 242 in the bottom wall 240 of the volute 200. The planar mating surface 252 is proximate to the outer surfaces 136 of the vanes 130, and has an inner perimeter 254. An inlet opening 256 of the volute is formed between the inner perimeter 254 and the hub 120 of the impeller 100.

The planar mating surface 252 is further comprised of a plurality of channels 260 extending radially from an inner channel end 262 at the inner perimeter 254 to an outer channel end 264 at the outer perimeter 258 of the planar mating surface 252. Each of the channels 260 includes a forward edge 266 in the direction 139 of impeller rotation. The channels 260 are oriented such that when the impeller 100 is rotated within the volute 200, for any vane 130, the leading edge 138 of the vane 130 traverses each channel 260 progressively from the inner end 262 of the channel 260 to the outer end 264 of the channel 260.

Referring in particular to FIGS. 5-7, in certain embodiments, the vanes 130 and the channels 260 may be arcuate in shape, with the leading edges 138 of the vanes 130 being convex edges, and the forward edges 266 of the channels 260 also being convex edges. (The forward edges 266 are the edges of the channels 260 that are opposite the direction of rotation of the impeller 100, i.e., the edges toward the leading edges 138 of the vanes 130.) In such a configuration, the angle of intersection of any vane 130 with any channel 260 decreases during progression of the intersection from the inner channel end 262 to the outer channel end 264. During rotation of the impeller 100, the angle of intersection of any vane 130 with any channel 260 may transition from an obtuse angle to an acute angle.

In certain embodiments, the proximal vane ends 132 may be contiguous with the central hub 120. The distal vane ends 134 may be contiguous with the outer perimeter 111 of the flange 110. The distal ends 134 of the vanes 130 may extend radially beyond the outer perimeter 258 of the planar mating surface 252 of the volute 200.

In certain embodiments, the number of vanes 130 may be between 1 and 11, and the number of channels 260 may be between 1 and 9. In other words, the impeller 100 may be a single vane impeller wherein the single vane spirals outwardly around the flange 110, and the planar mating surface

252 may have a single channel that spirals outwardly around it. The number of vanes **130** may be at least equal to the number of channels **260**.

In certain embodiments, the distance between the outer surfaces **136** of the impeller vanes **130** and the planar mating surface **252** of the volute **200** may be between 0.005 inches and 0.06 inches. Having a minimal vane-to-mating surface is advantageous with respect to pump efficiency, and in some embodiments, the clearance may be lesser. In general, the pump capacity is reduced by 1% for each additional 0.001 inches (0.025 mm) of impeller clearance.

The Applicants have determined that the width of the outer surfaces **136** of the impeller vanes **130** are affected by the manufacturing method, pumping media, and flow required. The size or outside diameter of the impeller **130** defines the head of the pump but a larger impeller will also flow more and thus require more power to drive. In some instances the flow of the pump may be reduced by narrowing the space between the vanes and thus increasing the size of the outer surfaces **136**. The design of the pump impeller **100** is a balance between motor size and desired output. Additionally, in some embodiments, the impeller **100** may have only a single vane which spirals outwardly around the flange **110** of the impeller. In general, across a range of pump applications, the width of the outer surfaces **136** of the impeller vanes **130** may be between 0.125 inches and 0.5 inches.

The Applicants have discovered that a pump **10** comprising an impeller **100** with vanes **130** and a volute **200** comprising a planar mating surface **252** with channels **260** operates in a manner in which solid particles suspended or entrained in the liquid to be pumped do not accumulate between the impeller and the volute. Accordingly, the pump operates more efficiently and uses less energy since a continuous liquid flow field is maintained proximate to the impeller, and drag on the impeller is reduced. Without wishing to be bound to any particular theory, the Applicants believe that the vanes **130** of the impeller **100** coat with the channels **260** in the planar mating surface **252** to continuously cause any solid particles that begin to adhere on or near the outer surfaces **136** of the vanes **130** to be dislodged and ejected out into the radial volume of the volute **200**, and on out of the volute **200** with other solids in the liquid being pumped.

The Applicants have further discovered that having channels **260** with excessive width decreases performance of the channels **260** and reduces pump efficiency. Thus the width and depth of the channels **260** should be minimized. In general, a channel width and depth of about 0.10" has been found to achieve the desired effect, although other channel sizes may be suitable depending upon the size and application of the particular pump.

In some embodiments, the channels **260** may be cast into the volute bottom cover **250**, and then the planar mating surface **252** may be machined to provide the channels **260** in final form. The Applicants have further discovered that it is preferable that the forward edges **266** are sharp in order to more effectively grab and tear off any material debris that has begun to accumulate on the impeller **100**; and that arcuate channels **260** mirrored to that of the impeller (as described previously) are most effective at removing debris, straight channels are also effective, and arcuate channels with curvature matching that of the impeller are least effective.

In certain embodiments, the planar mating surface **252** may be further comprised of a plurality of stub channels **268**, each of the stub channels **268** extending from the inner

perimeter **254** of the planar mating surface **252** to between one quarter and one half of the distance to the outer perimeter **258** of the planar mating surface **252**. The Applicants have discovered that the stub channels **268** are effective at preventing debris accumulation at the eye of the impeller, which is important for maintaining pump efficiency.

Referring now to FIGS. 1-8, in another aspect of the Applicants' liquid pump, the problem of reducing pump manufacturing and assembly cost while enabling greater precision of pump assembly is solved by providing a unitary pump volute **200** formed as a single piece and comprising certain features. Referring in particular to FIGS. 4, 7, and 8, the volute **200** of the pump is comprised of a volute chamber **202** comprising an upper wall **210**, a side wall **230**, an outlet passageway **235** in communication with the chamber **202**, and a lower wall **240**. A first annular structure **212** is comprised of a lower portion **213** including a lower side wall **215** and extending upwardly from the upper wall **210** of the volute chamber **202**. The first annular structure **212** is further comprised of an upper portion including an upper cylindrical cavity having a first annular side wall **214** and a bottom wall **216**.

A cylindrical passageway **218** extends from the bottom wall of the cylindrical cavity to the volute chamber **202**. The cylindrical passageway **218** may be partially bounded by a second annular side wall **220** which terminates at a planar bottom surface **222**.

A second annular structure **224** surrounds the first annular structure **212**, and extends upwardly from the upper wall **210** of the volute chamber **202**. The second annular structure **224** may be comprised of an outer cylindrical wall **226**. A planar flange **228** also surrounds the first annular structure. The inner perimeter **229** of the planar flange **228** may be contiguous with the outer cylindrical wall **226** of the second annular structure **224**.

As described previously, a through opening **242** is provided in the lower wall **240** of the volute chamber **202**. This opening **242** enables the installation of an impeller **100** on a pump motor shaft **32**, and further enables access to the impeller **100** if maintenance of the pump **10** is needed.

Referring to FIGS. 1-3, the pump **10** is further comprised of a motor housing **20** joined to the pump volute **200**. The motor housing **20** is comprised a lower planar surface **22** that is contiguous with the planar flange **228** of the pump volute **200**.

With regard to the pump volute **200**, the first annular side wall **214**, the cylindrical passageway **218**, the outer cylindrical wall **226**, and the lower through opening **242** have collinear central axes defining a common central axis **299**. The bottom wall **216** of the cylindrical cavity, the planar bottom surface **222**, and the planar flange **228** define planes parallel to each other and perpendicular to the common central axis **299**.

By making the pump volute **200** from a single piece of material, the planar surfaces, cylindrical cavities, and passageways of the volute **200** can be bored and/or milled on a single machine with great precision. Thus the problem of "tolerance stack up" that occurs when fitting together multiple volute pieces made on different machines is avoided. The motor housing, motor shaft bearing (which supports and aligns the motor shaft and stator), seal, and volute bottom cover plate are all located on these surfaces, cavities, and/or passageways. Fabricating the volute from a single piece of material such as cast iron, plastic, or a composite, enables all of these pieces to be properly aligned and squared relative to each other. This results in a reduction of pump manufactur-

ing and assembly cost while enabling greater precision of assembly of the pump and thus greater pump reliability.

Referring again to FIGS. 4 and 8, in another aspect of the Applicants' liquid pump, the problem of extending the life of a seal in the pump is solved by providing pump volute 200, a rotary shaft 32, and a rotary impeller 100 including certain features. The volute 200 is comprised of a volute chamber 202 having an upper wall 210 that includes an annular recess 204 surrounding a downward annular structure 220. A passageway 218 extends through the downward annular structure 220. The rotary shaft 32 of the pump motor 30 (FIG. 3) extends through the passageway 218 into the volute chamber 202. The rotary impeller 100 is joined to the rotary shaft 32 and is comprised of a flange 110 including an upward annular structure 112 that extends into the annular recess 204 of the upper wall 210 of the volute chamber 202.

The pump seal 40 is fitted to a lower edge or surface 222 of the downward annular structure 220 and prevents the leakage of fluid from the volute chamber 202 into the motor 30 and/or a housing 20 containing the motor 30. The location of the seal 40 on the lower edge 222 of the downward annular structure 220 positions the seal 40 such that it is disposed within the passageway 218 and surrounds a portion of the rotary shaft 32. The lower portion 42 of the seal extends into an annular cavity 206 that is formed between the rotary shaft 32 and the upward annular structure 112 of the impeller 100. In that manner, if the pump 10 temporarily runs dry or takes in some air, the seal 40 remains wetted, lubricated, and cooled by at least some liquid, thereby preventing damage to the seal 40 and extending its life. Additionally, from the upper side of the seal 40, during operation of the pump, oil from within the motor housing flows down through the ball bearing and cylindrical passageway 218 down to the shaft seal 40.

Additionally, the downward annular structure 220 and the annular recess 204 coact to greatly reduce the amount of solids in a liquid slurry in the volute chamber 202 that reaches the seal 40, while maintaining the seal 40 in a wet condition. By the configuration of the annular recess 204 of the volute 200, and the upward annular structure 112 of the impeller 100, the seal 40 is remotely located from the main portion of the volute chamber 202, and operates in a relatively low pressure environment. In that manner, the seal 40 is shielded from much of the solid debris in the liquid being pumped. Additionally, the Applicants have found that this configuration prevents any "roping" (i.e. string-like accumulation) of solids on the faces of the seal 40. Thus damage to the seal 40 is avoided, thereby extending seal life and overall pump reliability.

Referring now to FIGS. 2, 9A-9D, and 10A-10D, in another of the Applicants' liquid pump configured as a grinder pump, the problem of increasing pump efficiency by reducing energy consumption is solved by a solids cutting assembly 300 that has reduced drag in the liquid to be pumped. Thus the pump 10 requires less energy to accomplish the same amount of solids grinding and liquid pumping.

FIGS. 9A-9D depict a prior art cutting assembly 400 that is comprised of a rotary cutter 410 which coacts with a cutter plate 450 to cut solids in the liquid to be pumped. This cutting assembly is disclosed in commonly owned U.S. Pat. No. 7,159,806 of Ritsema, the disclosure of which is incorporated herein by reference. It can be seen that the cutter 410 is comprised of a plurality of blades 412 that cover a large portion of the cutting surface 452 of the cutter plate 450. This large amount of coverage of the cutter plate 450 by the blades 412 increases the operating friction of the cutter

assembly. Additionally, each of the blades 412 of the cutter 410 has a blunt profile as can be seen in the views of FIGS. 9C and 9D. This increases the amount of viscous drag from the liquid being pumped. Hence the increased drag and increased friction require more energy to operate this grinder pump.

Referring now to FIGS. 2 and 10A-10E, the Applicants' cutting assembly 300 is comprised of a rotatable drive shaft 32 and a rotary cutter 310 joined to the drive shaft 32. The rotary cutter 310 is comprised of a frustoconical hub 330 having a circular planar hub base 332, and a first cutting blade 312A and a second cutting blade 312B. Each of the cutting blades 312A and 312B is comprised of a planar blade base 314 defining a cutting plane and terminating at a cutting edge 316 that extends tangentially outwardly from the circular planar hub base 332. Referring in particular to FIGS. 10C-10E, the surface 305 of the planar blade base 314 may be minimized by providing hollowed-out cavities 307A and 307B on the cutting blades 312A and 312B. The Applicants have found that by reducing the surface area of the planar blade base 314, jamming of the rotary cutter against solid debris is reduced, resulting in more effective cutting. In certain embodiments, the width 309 of the planar blade base proximate to the cutting edges 316 may be about 0.1 inches wide.

The cutting assembly 300 of the pump 10 is further comprised of a cutter plate 350 comprising an outer planar cutter surface 352 that is parallel and proximate to the cutting plane defined by the planar blade bases 314 of the cutting blades 312A and 312B. Rotary motion of the rotary cutter 310 creates a shearing region between the cutting edges 316 of the cutter 310 and the cutter surface 352. To enhance cutting of the solids, the cutter surface 352 may be provided with a plurality of apertures such as V-slice apertures 354 disclosed in the aforementioned U.S. Pat. No. 7,159,806 of Ritsema.

In order to minimize the friction of the cutter 310 with the cutter surface 352 and to avoid jamming of solids between the cutter 310 and the cutter surface 352, the Applicants have found that it is desirable to minimize the "footprint" or contact patch of the blades on the cutter surface 352. This may be accomplished by providing a larger plurality of small blades (e.g., at least three small blades) than shown in FIGS. 3, 10A, and 10B, provided that such small blades have sufficient structural strength to withstand the forces required to cut the solids present. Alternatively, two blades 312A and 312B may be provided as shown in FIGS. 3, 10A, and 10B. In either case, it is desirable that the cutter blades have a low, streamlined profile as shown in FIGS. 10A-10E. This is in marked contrast to the relatively tall and blunt blades 412 of the prior art cutter assembly 400 of FIGS. 9A-9D.

In certain embodiments of the Applicants' low profile streamlined blades, at any radial distance along each cutting blade 312A and 312B, the ratio of the width 313 of the cutting blade 312A/312B to the thickness 315 of the cutting blade 312A/312B at that radial distance is at least about two, and preferably at least about three. Additionally, at any radial distance along each cutting blade, the maximum thickness 317 of the cutting blade may be located at least 70 percent across the cutting blade in the direction opposite the direction of rotation 319. The first and second cutting blades 312A and 312B may be further comprised of a first angled outer surface 318 terminating at the cutting edge 316. In such a configuration, the first angled outer surface 318 is on the leading side of the blade 312A/312B with respect to the direction of cutter rotation 319, and forms an acute angle 321 with the blade base 314. In certain embodiments, the

11

angle **321** may be less than 45 degrees. In one exemplary embodiment fabricated by the Applicants, the angle **321** was 33 degrees.

The first and second cutting blades **312A** and **312B** may be further comprised of a second angled outer surface **320** terminating at the blade base **314**. In such a configuration, the second angled outer surface **320** is on the trailing side of the blade **312A/312B** with respect to the direction of cutter rotation **319**, and may form an approximately perpendicular or obtuse angle **323** with the blade base.

In certain embodiments, the first and second cutting blades **312A** and **312B** may have a radially varying thickness from a maximum thickness at their innermost portions **322** proximate to the frustoconical hub **330** to one half of the maximum thickness at 60 percent of the distance to the outermost portion **324** of the first and second blades **312A** and **312B**. In one exemplary embodiment fabricated by the Applicants, the thickness of the blades **312A** and **312B** tapered to one half of their maximum thickness at 70 percent of the distance to their outermost portions **324**. The radial variation in thickness of the first and second cutting blades **312A** and **312B** may be linear between their innermost portions **322** and about 90 percent of the distance to their outermost portions **324**. The maximum thickness of the first and second blades **312A** and **312B** may be equal to the thickness of the frustoconical hub **330**.

In certain embodiments, the circular planar hub base **332** of the frustoconical hub **330** may be provided with an annular channel **334**, and radial connecting channels **336A** and **336B**, which extend from annular channel **334** to hollowed-out cavities **307A** and **307B** on the cutting blades **312A** and **312B**, respectively. The Applicants have discovered that providing such channels prevents and/or facilitates the discharge of any solid accumulation between the frustoconical hub **330** and the outer planar cutter surface **352**, thereby reducing operating friction and improving cutter efficiency.

The Applicants note that the above exemplary angles and ratios of the blades **312A** and **312B** of the rotary cutter **310** are in marked contrast to the blades **412** of the prior art cutter assembly **400** of FIGS. **9A-9D**. These blades **412** have a ratio of width to thickness of about 1.8, a maximum thickness that occurs at about the center of the blades **412**, an angle at the cutting edge of about 70 degrees, and taper radially to a half thickness at about 84 percent of their lengths. As noted previously, the cutter **410** has a plurality of blades **412** that have a large footprint on the cutter plate **450**, and are blunt rather than streamlined. Thus the Applicants' cutter **310** has less operating friction with its corresponding cutter plate **350**, and less drag in the liquid being pumped. Accordingly, the Applicants' cutter assembly **300** and pump **10** uses less energy to accomplish the same cutting and pumping results.

It is, therefore, apparent that there has been provided, in accordance with the present invention, liquid pumps having improved reliability, ease of assembly, increased precision of assembly, and/or lower manufacturing cost. Having thus described the basic concept of the invention, it will be rather apparent to those skilled in the art that the foregoing detailed disclosure is intended to be presented by way of example only, and is not limiting. Various alterations, improvements, and modifications will occur to those skilled in the art, though not expressly stated herein. These alterations,

12

improvements, and modifications are intended to be suggested hereby, and are within the spirit and scope of the invention. Additionally, the recited order of processing elements or sequences, or the use of numbers, letters, or other designations therefore, is not intended to limit the claimed processes to any order except as may be specified in the claims.

I claim:

1. A pump comprising:

- a) a motor housing comprising a lower planar surface and containing a motor comprised of a rotatable shaft;
- b) an impeller joined to a distal end of the rotatable shaft; and

- c) a unitary pump volute housing joined to the motor housing, the unitary pump volute housing formed as a single piece separate from the motor housing and comprised of:

- an upper wall, a side wall, and a lower wall extending radially inwardly from the side wall and comprising a lower surface and an upper surface opposite the upper wall, and bounded by a side edge surface defining a through opening sized to receive the impeller therethrough, wherein the upper, side, and lower walls define a volute chamber;

- a first annular structure extending upwardly from an inner region of the upper wall of the volute chamber and comprising a lower portion including a lower side wall and an upper portion including an upper cylindrical cavity comprised of a first annular side wall enclosed by a cylindrical outer surface, an annular top surface, and a cylindrical inner surface, and a bottom wall extending radially inwardly from the first annular side wall and terminating at a cylindrical passageway extending downwardly from the bottom wall; and

- a planar flange extending radially outwardly from the upper wall of the volute housing and contiguous with the lower planar surface of the motor housing, and surrounding the first annular structure, and having an inner perimeter;

wherein the first annular side wall, the cylindrical passageway, the rotatable shaft, the through opening, and the planar flange have collinear central axes defining a common central axis; and wherein the bottom wall of the upper cylindrical cavity, and the planar flange define planes parallel to each other and perpendicular to the common central axis.

2. The pump of claim 1, further comprising a second annular structure surrounding the first annular structure and extending upwardly from an outer region of the upper wall of the volute chamber.

3. The pump of claim 2, wherein the second annular structure is comprised of a cylindrical wall contiguous with the inner perimeter of the planar flange and having a central axis collinear with the common central axis.

4. The pump of claim 1, further comprising a cover removably disposed in the through opening and having a cover opening surrounding the common central axis.

5. The pump of claim 4, wherein the through opening is a cylindrical opening having a central axis collinear with the common central axis.

* * * * *